


TUBE:

Black, Smooth, Natural and Synthetic Rubber.

REINFORCEMENT:

High Tensile Textile Plies.

COVER:

Black, Smooth, Weather & Abrasion Resistant Rubber.
Fabric Impression.

TEMP RANGE:

-30°C Approx to +70°C Approx.

APPLICATIONS:

For Water Cleaning Equipment.
For High Pressure Washing .
High Pressure Spray of Agricultural Pesticides.

PROPERTIES:

Seamless
Uniform Thickness
Smooth Bore
Mandrel Built

FEATURES:

Good Abrasion Resistance
Heavy Wall Thickness

STANDARD COLOUR:

Black

MARKING ON THE HOSE:

Hi Power Super Spray Hose ID...WP
1000 PSI Made in India

APPLICABLE STANDARDS:

IS : 1677/1968 TYPE IIIA



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1SS10	10.00	20.00	5.00	70 1000	280 4000	102	0.38	-	-	YES	5
1SS12.5	12.00	23.50	5.50	70 1000	280 4000	127	0.39	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).
In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.