


**TUBE:**

Thin & Very Smooth plasticized PVC Wall  
Specially Compounded Rigid PVC

**REINFORCEMENT:**

Reinforcement Which Is Helically Wound  
& Inseparably Fused To Soft Inner Walls

**COVER:**

Wall: PVC

**TEMP RANGE:**

-10 °C Approx. To +60/70 °C Approx.

**APPLICATIONS:**

Cold Or Warm Air Installations Of Various Kinds.  
Cooling Of Motors & Air Intakes For All Types  
Of Machinery & Equipments.  
Conveying Warm Air For Drying Purposes.  
Removing Fumes From Factories, Fuel  
Tanks & Underground Installations.  
Transportation Of Powders, Gases & Liquids.  
Collection Of Fibre Waste, Sawdust, Wood  
Shavings & Dust Collections of Metal Grinders.

**PROPERTIES:**

Strong Resistance To Most Chemicals  
Acids & Alkalies.  
Abrasion Resistant  
Crush Prad Kink Pad

**FEATURES:**

Light Weight  
Highly Flexible

**STANDARD COLOUR:**

Grey

**MARKING ON THE HOSE:**

ASHISH REALFLEX DUCT HOSE (VACUUM)

MFG. AAPL (INDIA) CODE....



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
4DUCT50HD	50.80 ± 0.5	58.20 ± 0.5	3.70	-	-	-	-	65	-	30	-	NO	60
4DUCT63HD	63.00 ± 0.5	72.00 ± 0.5	4.50	-	-	-	-	85	-	30	-	NO	60
4DUCT75HD	76.50 ± 0.5	84.54 ± 0.5	4.02	-	-	-	-	95	-	30	-	NO	30
4DUCT100HD	101.20 ± 0.5	111.94 ± 0.5	5.37	-	-	-	-	125	-	30	-	NO	30
4DUCT125HD	127.00 ± 0.7	137.20 ± 0.7	5.10	-	-	-	-	140	-	15	-	NO	15
4DUCT150HD	152.40 ± 0.7	163.10 ± 0.7	5.35	-	-	-	-	205	-	15	-	NO	15
4DUCT200HD	204.00 ± 1.5	216.40 ± 1.0	6.20	-	-	-	-	270	-	15	-	NO'	15

Specification Subject to change due to Improvement in Quality ( E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.