


TUBE:

Strong, Flexible & Smooth Plasticized PVC.

REINFORCEMENT:

Hard Rigid PVC Spiral

COVER:

Hard Rigid PVC

TEMP RANGE:

-10 °C Approx. To +70 °C Approx.

APPLICATIONS:

Strongly Recommended For Conveying Diesel Fuels, Kerosene Liquid Petroleum Products, Lubricating Oil, Mineral Oils, Light Oils, Transformer etc.

PROPERTIES:

 Resistant To Oil & Other Chemicals.
 Resistant To Absolute Vacuum, Easy To Handle.
 Quite Tough: Tough Enough To Resist Distortion Under Impact & Crush Loads During Service.

FEATURES:

 Flexibility: Specially Designed To Have Greater Flexibility Than Rubber & Hose Can Be Bent As Desired In Practical Uses.
 Smooth Inside Surface Results In Quick Conveyance Of Fluids, This Means Minimum Friction Loss, Saves Higher Energy & High Flow Rate.

STANDARD COLOUR:

Blue

MARKING ON THE HOSE:

 ASHISH REALFLEX OIL-HOSE (BLUE) MFG.AAPL
 (INDIA) CODE....


ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	S	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
4OIL25	25.40 ± 0.5	31.50 ± 0.5	3.05	8 115	24 345	48	0.35	30	-	NO	150
4OIL30	31.80 ± 0.5	38.80 ± 1.5	3.50	7 100	21 300	68	0.45	30	-	NO	90
4OIL40	38.00 ± 0.5	46.30 ± 1.5	4.15	5.5 80	16.5 240	70	0.77	30	-	YES	90
4OIL50	50.80 ± 0.5	60.80 ± 1.5	5.00	4.5 65	13.5 195	100	1.17	30	-	YES	30
4OIL65	63.50 ± 1.0	74.50 ± 1.5	5.50	4.5 65	13.5 195	120	1.45	30	-	YES	30
4OIL75	76.20 ± 1.0	87.20 ± 1.5	5.50	4.5 65	13.5 195	155	1.93	30	-	YES	30
4OIL100	101.20 ± 2.0	114.20 ± 2.0	6.50	4 60	12 180	213	3.00	30	-	NO	30

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.