


**TUBE:**

Black Antistatic Smooth Nitrile Rubber Resistant to Oil, Gasoline & Diesel.

**REINFORCEMENT:**

Reinforcement: High Strength Steel Wire Braid

**COVER:**

Black Synthetic Rubber Cover Resistant to Weather & Petroleum based Fuel  
Fabric Impression

**TEMP RANGE:**

-40°C to +55°C

**APPLICATIONS:**

For all Types of Gasoline Dispensing Applications

**PROPERTIES:**

Seamless  
Uniform Thickness  
Smooth Bore  
Flame Retardant

**STANDARD COLOUR:**

Black

**MARKING ON THE HOSE:**

Indo- Maksson Floil Fuel Dispensing Hose  
ID....WP India

**APPLICABLE STANDARDS:**

BS EN 1360 TYPE III

ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1PTR20	19.10	29.50	5.20	16 232	48 696	152	-	-	-	YES	1
1PTR25	25.40	36.00	5.30	16 232	48 696	203	-	-	-	YES	1

Specification Subject to change due to Improvement in Quality ( E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.