


TUBE:

- ▶ Smooth Plasticized & Rubberized Mixed Compound
- ▶ Smooth Interior

REINFORCEMENT:

- ▶ Fabric Reinforced

COVER:

- ▶ Smooth Plasticized & Rubberized Mixed Exterior Wall

TEMP RANGE:

- ▶ -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- ▶ Multipurpose Hose for Air, Pneumatic, Heavy Duty Delivery of Water & Chemicals

PROPERTIES:

- ▶ Optimized Flow Properties
- ▶ Good Resistance To Alkali, Acids, UV, Ozone, Oil, Chemicals & Moisture.
- ▶ Gas & Liquid Tight
- ▶ Crush-Proof & Kink Resistant

FEATURES:

- ▶ Highly Flexible
- ▶ Small Bending Radius
- ▶ Abrasion Resistant
- ▶ Strong Enough To Withstand High Pressure, Total Consolidation & Adhesion Levels Are Superb.

STANDARD COLOUR:

- ▶ Blue

MARKING ON THE HOSE:

- ▶ Duplon Super High Pressure Air Hose Size.... WP



ITEM	ID	OD	WALL THICKNES S	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
2AIR8	7.90	14.30	3.20	40 575	150 2175	-	-	100	-	YES	100
2AIR10	9.50	16.00	3.25	40 575	150 2175	-	-	100	-	YES	100
2AIR12	12.70	20.70	4.00	40 575	150 2175	-	-	100	-	YES	100

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.