

HDPE EL RIGID BEND HOSE



TUBE:

► Wall : HDPE

REINFORCEMENT:

► Interlocking Rigid HDPE Profile

COVER:

► Wall : HDPE

TEMP RANGE:

► -20 °C Approx. to +70 °C Approx.

APPLICATIONS:

- For Air, Fume Extraction & Liquid Supply Under Low Pressure.
- For Conveyance Of Powders, Granules & Dust Extraction.
- For Woodworking Dust
- Portable Air Conditioner Venting Hose

PROPERTIES:

- Super Resistance To Alkalis , Acids, Chemicals, UV & Ozone.
- Self-Supporting
- Simple Increase Or Reduction Of Size
- Maintains Shape
- Electrical & Surface Resistance $\leq 10^6 \Omega$

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

Na



ITEM	ID	OD	WALL THICKNES S	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11RBHDPE51	51.00	57.00	-	- -	- -	-	-	5	-	NO	5
11RBHDPE65	65.00	71.00	-	- -	- -	-	-	5	-	NO	5
11RBHDPE76	76.00	83.00	-	- -	- -	-	-	5	-	NO	5
11RBHDPE90	90.00	97.00	-	- -	- -	-	-	5	-	NO	5
11RBHDPE102	102.00	109.00	-	- -	- -	-	-	5	-	NO	5
11RBHDPE127	127.00	135.00	-	- -	- -	-	-	5	-	NO	5
11RBHDPE152	152.00	160.00	-	- -	- -	-	-	5	-	NO	5
11RBHDPE203	203.00	211.00	-	- -	- -	-	-	5	-	NO	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No: 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558