


TUBE:

► Oil Resistant Synthetic Rubber

REINFORCEMENT:

► Four Or Six High Tensile Steel Spirals

COVER:

► Environment & Oil Resistant
 ► Synthetic Rubber

TEMP RANGE:

► -40°C to +121°C

APPLICATIONS:

► Very High Pressure Power Lines
 ► Suitable for Impulse Surge Lines with more Life Cycles
 For use with Petroleum, Synthetic or Water based fluids

FEATURES:

► Weather, Abrasion & Oil Resistant

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

► HoseX 6S DN40 EXCEEDS SAE J517 100 R15
 1.1/2"-38.1 MM-WP 42Mpa/420 Bar/
 6090 PSI-MSHA

APPLICABLE STANDARDS:

► SAE J 517 - 100 R15
 ► ISO 3862



WALL
THICKNES
S

ITEM	ID	OD	WALL THICKNES S	WORKING PRESSURE	PSI	BURSTING PRESSURE	PSI	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
501R1516	25.70	38.90	6.60	420	6090	1680	24360	330	2.28	40	-	NO	1
501R1520	32.20	48.40	8.10	420	6090	1680	24360	445	4.27	40	-	NO	1
501R1524	38.50	58.00	9.75	420	6090	1680	24360	530	5.75	40	-	YES	1
501R1532	51.20	71.20	10.00	420	6090	1680	24360	600	8.22	40	-	YES	1

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.