


TUBE:

Specially Compounded Synthetic Rubber, Black

REINFORCEMENT:

Braiding of High Strength Synthetic Fibre

COVER:

Black Rubber Cover, Wrap Finish

TEMP RANGE:

-30°C Approx to +82°C Approx

APPLICATIONS:

For All Types of Industries & Pneumatic Tools that Use Compressed Air Applications

PROPERTIES:

Seamless

Uniform Thickness

Flexible

STANDARD COLOUR:

Inner Tube - Black

Outer Cover - Black

MARKING ON THE HOSE:

Indo Maksson Super Power Pneumatic Tool Hose

Made in India

APPLICABLE STANDARDS:

IS : 446 Type II



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1PT6	6.00	15.00	4.50	14 200	56 800	76	0.19	-	-	YES	5
1PT8	8.00	16.00	4.00	14 200	56 800	102	0.25	-	-	YES	5
1PT10	10.00	18.00	4.00	14 200	56 800	102	0.28	-	-	YES	5
1PT12.5	12.50	22.00	4.75	14 200	56 800	127	0.36	-	-	YES	5
1PT16	16.00	-	-	14 200	56 800	-	-	-	-	YES	5
1PT20	19.00	29.50	5.25	14 200	56 800	152	0.58	-	-	YES	5
1PT25	25.40	37.00	5.80	14 200	56 800	203	0.77	-	-	YES	5
1PT31.5	31.00	43.50	6.25	14 200	56 800	254	1.00	-	-	YES	5
1PT38	38.00	51.50	6.75	14 200	56 800	305	1.20	-	-	YES	5
1PT50	50.00	65.00	7.50	14 200	56 800	305	1.80	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.