

J 2-7 PU L ANTISTATIC SUCTION HOSE



TUBE:

Special Premium Ether-Polyurethane with Smooth Interior Wall
 Wall Thickness 0.9mm Approx

REINFORCEMENT:

Copper Coated Spring Steel Wire Integrated in the Wall

TEMP RANGE:

-40 °C Approx. to +90 °C Approx.
 Short Time to +125 °C Approx.

APPLICATIONS:

For Abrasive Solids such as Dust, Powder, Fibers, Chip and Granulates.
 For Gaseous and Liquid Media
 For De-Dusting and Suction Plants, Industrial Vacuum Cleaner.
 Suction of Paper and Textile Fibers as Resistant Protection Hose.

PROPERTIES:

Food Grade and Complies to FDA 21 CFR 177.2600
 Highly Abrasion Proof
 Optimized Flow Properties
 Smooth Interior Layer
 High Tensile Strength & tear Resistant
 Microbe & Hydrolysis Resistant
 Good Resistance to Chemicals
 Good Resistance to UV & Ozone
 Small Bending Radius
 Kink-Proof
 Gas and Liquid Tight
 Capable of Electrostatic Discharge by Grounding the Spiral
 Electrical & Surface Resistance $\leq 10^{10} \Omega$

STANDARD COLOUR:

Transparent

MARKING ON THE HOSE:

NA



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11PULS40(AS)	40.00	48.00	0.90	1.80	26	-	-	-	0.35	15	0.43	YES	1
11PULS45(AS)	45.00	53.00	0.90	1.11	16	-	-	-	0.38	15	0.40	YES	1
11PULS51(AS)	51.00	59.00	0.90	1.37	20	-	-	-	0.41	15	0.37	YES	1
11PULS55(AS)	55.00	63.00	0.90	0.79	11	-	-	-	0.46	15	0.33	YES	1
11PULS60(AS)	60.00	68.00	0.90	1.15	17	-	-	-	0.49	15	0.29	YES	1
11PULS63(AS)	63.00	71.00	0.90	1.05	15	-	-	-	0.52	15	0.21	YES	1
11PULS76(AS)	76.00	85.00	0.90	0.92	13	-	-	-	0.63	15	0.20	YES	1
11PULS80(AS)	80.00	89.00	0.90	0.85	12	-	-	-	0.68	15	0.19	YES	1
11PULS90(AS)	90.00	99.00	0.90	0.77	11	-	-	-	0.75	15	0.16	YES	1
11PULS102(AS)	102.00	111.00	0.90	0.69	10	-	-	-	0.97	15	0.12	YES	1
11PULS127(AS)	127.00	136.00	0.90	0.56	8	-	-	-	1.22	15	0.09	YES	1
11PULS152(AS)	152.00	161.00	0.90	0.46	7	-	-	-	1.52	15	0.08	YES	1
11PULS203(AS)	203.00	212.00	0.90	0.35	5	-	-	-	2.00	15	0.05	YES	1

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No: 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558