

J 2-8 PU H ANTISTATIC SUCTION HOSE



TUBE:

Special Premium Ester-Polyurethane with Smooth Interior Wall
 Wall Thickness 1.5mm Approx

REINFORCEMENT:

Copper Coated Spring Steel Wire Integrated in the Wall

TEMP RANGE:

-40 °C Approx. to +90 °C Approx.
 Short Time to +125 °C Approx.

APPLICATIONS:

For High Flow-Rates of Hot & Abrasive Solids such as Powder, Chip & Granules
 For Industrial Vacuum Cleaners, Granule Conveying Systems, Printing Machines, Blowers & Compressors
 As Robust Protection Hose

PROPERTIES:

Food Grade and Complies to FDA 21 CFR 177.2600
 Heavy Model
 Highly Abrasion Proof
 Optimized Flow Properties
 Smooth Interior Layer
 Increased Pressure & Vacuum Resistance
 High Tensile Strength & tear Resistant
 Microbe & Hydrolysis Resistant
 Good Resistance to Chemicals
 Good Resistance to UV & Ozone
 Small Bending Radius
 Kink-Proof
 Gas and Liquid Tight
 Capable of Electrostatic Discharge by Grounding the Spiral
 Electrical & Surface Resistance $\leq 10^{10} \Omega$

STANDARD COLOUR:

Transparent

MARKING ON THE HOSE:

NA



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11PUHS40(AS)	40.00	48.00	1.50	3.93	57	-	-	-	0.55	15	0.86	YES	1
11PUHS45(AS)	45.00	53.00	1.50	3.13	45	-	-	-	0.60	15	0.85	YES	1
11PUHS51(AS)	51.00	59.00	1.50	2.33	34	-	-	-	0.66	15	0.84	YES	1
11PUHS55(AS)	55.00	63.00	1.50	1.35	20	-	-	-	0.72	15	0.79	YES	1
11PUHS60(AS)	60.00	68.00	1.50	1.96	28	-	-	-	0.78	15	0.73	YES	1
11PUHS63(AS)	63.00	71.00	1.50	1.82	26	-	-	-	0.84	15	0.68	YES	1
11PUHS76(AS)	76.00	85.00	1.50	1.58	23	-	-	-	1.05	15	0.56	YES	1
11PUHS80(AS)	80.00	89.00	1.50	1.58	23	-	-	-	1.15	15	0.50	YES	1
11PUHS90(AS)	90.00	99.00	1.50	1.30	19	-	-	-	1.25	15	0.43	YES	1
11PUHS102(AS)	102.00	111.00	1.50	1.19	17	-	-	-	1.49	15	0.36	YES	1
11PUHS152(AS)	152.00	161.00	1.50	0.80	12	-	-	-	2.41	15	0.18	YES	1

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No: 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558