

DUCT HOSE GREY





- ► Thin & Very Smooth Plasticized PVC Wall
- ► Specially Compounded Rigid PVC

REINFORCEMENT:

Reinforcement Which Is Helically Wound
& Inseparably Fused To Soft Inner Walls.

COVER:

► Wall: Corrugated PVC

TEMP RANGE:

► -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- ► Cold Or Warm Air Installations Of Various Kinds.
- ► Cooling Of Motors & Air Intakes For All Types Of Machinery & Equipments.
- ► Conveying Warm Air For Drying Purposes.
- ▶ Removing Fumes From Factories, Fuel Tanks & Underground Installations.
- ► Transportation of Powders Gases & Liquids.
- ► Transportation Of Wheat & Other Serials In Course Of Processing.
- ► Removel of Particles Erected in Stone-Masoning, Fibre Glass & Asbestos Processing.
- ► General Dust Collection, Domestic Vaccum Cleaning Equipments & Heavy Duty Dust Extraction.
- ► Ventilation & Heating Systems In Domestic, Commercial & Industrial Locations.
- ► Collection of Fibre Waste, Sawdust, Wood Shavings & Dust Collections of Metal Grinders.

PROPERTIES:

- ► Strong Resistance To Most Chemicals, Acids & Alkalies.
- ► Abrasion Resistant
- ► Crush Proof & Kink Proof

FEATURES:

- ► Light Weight
- ► Highly Flexible



STANDARD COLOUR:

▶ Grey

MARKING ON THE HOSE:

► Dutron Kanaflex Duct Hose Size... India



DUTRON

DUCT HOSE GREY























			WALL										
			THICKNES	WOR	KING	BURS	ΓING	BENDING		STANDARD	VACCUM		
ITEM	ID	OD	S	PRES	SURE	PRESS	URE	RADIUS	WEIGHT	LENGTH	PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar		mtr
2DUCT16	16.00	22.00	-	-	-	-	-	22	-	30	-	NO	30
2DUCT22	21.00	28.60	-	-	-	-	-	35	-	30	-	NO	30
2DUCT25	25.40	32.10	-	-	-	-	-	45	-	30	-	NO	30
2DUCT30	31.80	38.64	-	-	-	-	-	50	-	30	-	NO	30
2DUCT40	38.00	45.00	-	-	-	-	-	55	-	30	-	YES	1
2DUCT50	50.80	57.20	-	-	-	-	-	65	-	30	-	YES	1
2DUCT60	60.50	68.50	-	-	-	-	-	75	-	30	-	YES	1
2DUCT63	63.00	70.50	-	-	-	-	-	85	-	30	-	YES	1
2DUCT75	76.50	83.54	-	-	-	-	-	95	-	30	-	YES	1
2DUCT80	80.00	87.04	-	-	-	-	-	100	-	30	-	NO	30
2DUCT90	90.00	97.04	-	-	-	-	-	110	-	30	-	YES	1
2DUCT100	101.20	108.94	-	-	-	-	-	125	-	30	-	YES	1
2DUCT110	110.00	117.74	-	-	-	-	-	130	-	30	-	NO	30
2DUCT125	127.00	135.20	-	-	-	-	-	140	-	15	-	YES	1
2DUCT140	140.00	148.20	-	-	-	-	-	150	-	15	-	NO	15
2DUCT150	152.40	161.10	-	-	-	-	-	205	-	15	-	YES	1
2DUCT160	160.00	168.70	-	-	-	-	-	210	-	15	-	YES	1
2DUCT200	204.00	214.40	-	-	-	-	-	270	-	15	-	YES	1
2DUCT225	225.00	-	-	-	-	-	-	320	-	10	-	NO	10
2DUCT250	253.00	264.00	-	-	-	-	-	370	-	10	-	YES	1
2DUCT300	305.00	320.00	-	-	-	-	-	370	-	10	-	YES	1

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.