

FLAT HOSE

DUPLON



TUBE:

- Flexible Smooth Plasticized PVC
- Inner Surface Smooth Highly Flexible

REINFORCEMENT:

- Synthetic Yarn Reinforcement

COVER:

- Smooth Plasticized PVC

TEMP RANGE:

- -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- In Agriculture Use Mainly As Delivery Hose
- At Construction Sites, Mines & Quarries, Flushing Is Faster.
- For Transferring Corrosive Chemicals & Liquids In Chemical Factories.
- Ideal For Use As Drainage Hose In Emergency / Flood / Disaster Situations When Large Quantities Of Water Must Be Moved Quickly.

PROPERTIES:

- Extruded In Long Continuous Process For Optimum Choice Of Lengths.
- Tough & Puncture Proof. Can resist External Pressure & Abrasion In Use Gives A Long Service Life.
- Can Carry Water / Liquids In Higher Heads & In Hilly Areas Without Inflation.

FEATURES:

- Requires No Maintenance .Do Not Rust Corrode Or Require Cathodic Protection.
- Roll Up Easily, Requires Minimum Storage Space.And Is Light Weight Too.
- Remains Soft & Pliable Even In Extremely Cold Weather & At Below Freezing Temperature.

STANDARD COLOUR:

- Blue

MARKING ON THE HOSE:

- Duplon Flat Hose Made In India



ITEM	ID	OD	THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
2FLAT25	26.00 ± 1	28.00 ± 1	1.00 ± 0.1	4 58	12 174	-	-	60	-	YES	60
2FLAT40	41.00 ± 1	43.00 ± 1	1.00 ± 0.1	4 58	12 174	-	-	60	-	YES	60
2FLAT50	53.00 ± 1	55.20 ± 1	1.10 ± 0.1	3 44	9 130	-	-	60	-	YES	60
2FLAT65	66.00 ± 1	68.40 ± 1	1.20 ± 0.1	3 44	7 100	-	-	60	-	YES	60
2FLAT75	82.00 ± 1	84.40 ± 1	1.20 ± 0.1	3 44	7 100	-	-	60	-	YES	60
2FLAT100	104.00 ± 2	106.40 ± 2	1.20 ± 0.1	3 44	7 100	-	-	60	-	YES	60
2FLAT150	154.00 ± 3	157.60 ± 3	1.80 ± 0.1	3 44	6 87	-	-	60	-	YES	60
2FLAT200	204.00 ± 3	208.60 ± 3	2.30 ± 0.2	2 29	4 58	-	-	50	-	YES	50
2FLAT250	257.00 ± 3	262.00 ± 3	2.50 ± 0.2	2 29	3 44	-	-	50	-	YES	50
2FLAT300	310.00 ± 3	315.40 ± 3	2.70 ± 0.3	2 29	3 44	-	-	50	-	NO	50

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

Kotak Mahindra Bank A/c No. 9945093528

RTGS/NEFT IFSC:KKBK0000191